



# PRODUCT PROFILE

## Zebra® EvapoTreat™

### Pretreat & Transfer Waste Fluids for Evaporation Efficiency

- Combines oil skimming and waste fluids transfer into a single unit
- Increase evaporation rate by removing surface oils which prevent water-based fluid from vaporizing efficiently
- Prevent sludge accumulation and maintenance
- Reduce hot plate or burner cleaning and replacement
- Increase value of segregated waste oil
- Easily mounts to drums, totes, or other wastewater holding vessels

Removes surface oils using the Zebra Belt Skimmer.

Our 1" wide, 18" reach, poly belt unit, which removes 1 gallon of oil per hour, is standard and requires only a 2" diameter opening.

A 2' oil discharge hose is provided (not shown).



Rugged, electric diaphragm pump transfers the cleaned fluid to your evaporation station.

1.5 gpm, 115v, 60Hz, with 23' waterlift and 3/8" FPT outlet fitting.

Transfer hose not included.

Quickly mounts to any 1/4" wall using Zebra Lockjaw™

Clean fluid lifted from holding vessel (6' flexible hose included)

Model	Part Number	Description
EvapoTreat System	EVXET.1	EvapoTreat System to pretreat and transfer waste fluid to any evaporation station. Includes Zebra Belt Skimmer, Lockjaw Mounting Clamp, electric diaphragm pump, and fluid intake hose.

Zebra Skimmers Corporation  
 PO Box 833 Chagrin Fall, OH 44022 USA  
[www.ZebraSkimmers.com](http://www.ZebraSkimmers.com)  
[www.CoolantMaintenance.com](http://www.CoolantMaintenance.com)  
 Phone: 1-440-349-0141  
 Toll Free: 1-888-249-4855  
 Fax: 1-440-349-1211  
 ©December 2008 Zebra Skimmers Corp. All rights reserved.

Contact your Zebra distributor for more information.