



SPECIFICATIONS & PARTS

Zebra® Circulation Pumps

FXP Series - Technical Specifications

Part Number	FXP3.1	FXP5	FXP3.1E	FXP5E
Power:	115v	115v	230v	230v
Hertz:	60	60	50/60	50/60
Watts:	30	208	30	208
Amps:	.5	3.2	.4/3	1.4/1.7
Horsepower:	1/160	1/160	1/160	1/15
Flowrate, @ 1':	2 gpm (7.5 lpm)	11 gpm (41.6 lpm)	2 gpm (7.5 lpm)	11 gpm (41.6 lpm)
Max Lift:	4.6' (1.4m)	20' (6.1m)	4.6' (1.4m)	20' (6.1m)
Max Particle Size:	1/8" (3.2mm)	1/8" (3.2mm)	1/8" (3.2mm)	1/8" (3.2mm)
Body Materials:	Nylon	Epoxy coated cast Al	Nylon	Epoxy coated cast Al
Internal Materials:	Glass-filled nylon	Nylon/Viton	Glass-filled nylon	Nylon/Viton
Max Operating Temp:	120°F (49°C)	120°F (49°C)	120°F (49°C)	120°F (49°C)
Cord Length:	10' (3m)	10' (3m)	12' (3.6m)	10' (3m)
Discharge Port:	1/4" MNPT	1/2" MNPT	1/4" MNPT	1/2" MNPT
Weight:	3.17 lbs. (1.44kg)	8.25 lbs. (3.7kg)	3.17 lbs. (1.44kg)	8.25 lbs. (3.7kg)
Dimensions, in.:	3.88 x 3 x 3.88	7 x 4.4 x 5.4	3.88 x 3 x 3.88	7 x 4.4 x 5.4
Dimensions, cm.:	9.9 x 7.6 x 9.9	18 x 10 x 14	9.9 x 7.6 x 9.9	18 x 10 x 14



FXP3.1



FXP5

FXP Series - Replacement Parts & Accessories

Individual pump components are not sold separately

Zebra Skimmers Corporation
 PO Box 833 Chagrin Falls, OH 44022
www.ZebraSkimmers.com
www.CoolantMaintenance.com
 Toll Free 888-249-4855
 Phone: 440.349.0141
 Fax: 440.349.1211

©November2007 Zebra Skimmers Corp. All rights reserved.

Contact your distributor
for more information